

STANDARD CHAMBER FURNACES

Model	Max. Temp. °C	Cont. Temp. °C	Time to max.temp (mins)	Inner Dimen. (cm) H x W x D	Inner Vol. (ltr)	Max. Power (KW)	Ex. Dims. (cm) H x W x D	Phase
PLF 110/6	1100	1050	65	15x21x20	6.30	1.5	65x55x58	1
PLF 110/8	1100	1050	65	18x21x20	7.50	2.0	65x55x58	1
PLF 110/10	1100	1050	55	20x20x25	10.00	3.0	72x56x67	1
PLF 110/15	1100	1050	45	23x22x30	15.00	4.0	72x56x67	1
PLF 110/30	1100	1050	45	28x28x38	28.00	4.0	79x59x70	1
PLF 110/45	1100	1050	60	30x30x50	45.00	6.0	77x66x72	3
PLF 115M	1150	1100	100	11x21x28	6.50	2.7	65x55x58	1
PLF 120/5	1200	1150	50	14x18x20	5.00	2.0	65x55x58	1
PLF 120/7	1200	1150	60	14x20x25	7.30	2.0	65x55x58	1
PLF 120/10	1200	1150	40	20x20x25	10.00	4.0	72x56x67	1
PLF 120/12	1200	1150	50	20x20x30	12.00	4.0	72x56x67	1
PLF 120/15	1200	1150	60	23x22x30	15.00	4.0	72x56x67	1
PLF 120/18	1200	1150	70	23x23x35	18.00	4.0	79x59x70	3
PLF 120/27	1200	1150	80	28x28x35	27.40	4.5	79x59x70	3
PLF 120/45	1200	1150	70	30x30x50	45.00	6.0	77x66x72	3
PLF 130/6	1300	1250	65	14x20x25	6.30	2.5	65x55x58	1
PLF 130/9	1300	1250	50	18x20x25	9.00	4.0	72x56x67	1
PLF 130/12	1300	1250	45	20x20x30	12.00	4.0	72x56x67	1
PLF 130/15	1300	1250	60	23x23x30	15.00	4.0	72x56x67	1
PLF 130/18	1300	1250	65	23x23x35	18.00	4.0	79x59x70	1
PLF 130/25	1300	1250	50	27x27x35	24.60	6.0	79x59x70	3
PLF 130/45	1300	1250	90	30x30x50	45.00	6.0	77x66x72	3
PLF 140/5	1400	1400	45	14x15x25	5.30	3.0	65x54x58	1
PLF 140/9	1400	1400	60	18x20x25	9.00	4.0	72x56x67	1
PLF 140/15	1400	1400	75	22x22x31	15.00	9.0	77x60x75	3
PLF 140/33	1400	1400	135	27x25x48	32.50	12.0	77x60x75	3
PLF 150/5	1500	1450	65	14x15x25	5.30	3.5	72x56x67	3
PLF 150/7	1500	1450	75	14x20x25	7.00	4.8	72x56x67	3
PLF 150/9	1500	1450	90	18x20x25	9.00	5.2	72x56x67	3
PLF 150/15	1500	1450	75	22x22x31	15.00	9.0	77x60x75	3
PLF 150/24	1500	1450	135	27x25x36	24.30	10.4	77x60x75	3
PLF 150/30	1500	1450	155	27x25x44	29.70	12.0	77x60x75	3
PLF 160/5	1600	1550	75	14x15x24	5.30	4.9	65x55x58	3
PLF 160/7	1600	1550	70	17x17x24	6.90	5.3	72x56x67	3
PLF 160/9	1600	1550	85	18x21x24	8.60	5.8	72x56x67	3
PLF 160/15	1600	1550	90	22x22x31	15.00	10.0	77x60x75	3
PLF 160/25	1600	1550	140	26x25x38	23.40	11.6	77x60x75	3
PLF 160/30	1600	1550	155	26x25x46	27.30	12.5	77x60x75	3
PLF 160/35	1600	1550	165	25x30x47	35.25	14.5	77x65x75	3
PLF 160/40	1600	1550	180	30x30x45	40.50	16.0	82x65x80	3